



GP

GENERAL PETROLEUM

www.generalpetroleum.de

Product Data Sheet (PDS)



DEOGEN SYNTHETIC 15W40 CJ-4

Published By:

Technical Department of
General Petroleum GmbH
Frankfurt, Germany

Last Update Date:

1/8/2019

DEOGEN SYNTHETIC SAE 15W40 API CJ-4



DEOGEN Synthetic 15W-40 is the premium choice for API CJ-4 emission-quality diesel oil required for newer diesel engines, as well as older diesel applications (including those equipped with turbochargers). It delivers extraordinary lubrication in diesel engines found in commercial, fleet and personal vehicles. Formulated with the latest additive and synthetic base oil technology, DEOGEN Synthetic 15W-40 exceeds the higher performance demands of modern engines. It withstands the stress of heat, soot and acids to help prevent deposits, corrosion and wear. It is compatible with all exhaust treatment devices and have fuel economy performance.

PERFORMANCE STANDARDS:

GP DEOGEN SYNTHETIC 15W40 CJ-4 meets and exceeds the following Industry Specifications:

- ACEA E9,E7
- API CJ-4,
- Cummins CES 20081,
- Detroit Diesel DDC 93K218
- MB 228.31,
- Volvo VDS-4, VDS-3
- Renault RLD-3,
- Caterpillar ECF-3
- Caterpillar ECF-2
- MAN M3275
- Mack EO-M Plus

FEATURES & BENEFITS:

GP DEOGEN SYNTHETIC 15W40 CJ-4 provides:

- Excellent engine cleanliness through advanced soot handling technology.
- Mixed fleet capabilities.

DEOGEN SYNTHETIC SAE 15W40 API CJ-4



- Exceptional low engine wear.
- Trouble free operation between long drain service intervals.
- Reduced maintenance capabilities.
- Low Oxidation
- All season engine oil

APPLICATIONS:

- Commercial road transport, including the latest engines fitted with exhaust cleanup devices of all types
- Mixed fleets of both diesel and gasoline engines, and both old and new equipment
- Stop-and-go vehicles in high soot loading service such as buses and waste collection trucks
- Most modern off-highway engines including those adapted for current and future emissions standards

TECHNICAL DATA

Sr. No	Characteristics	Test Method	Results
01	Appearance	VISUAL	B & C
03	Color	ASTM D-1500	3.5
04	Density @ 15 C, g/ml	ASTM D-4052	0.877
05	Viscosity @ 40 C, cSt	ASTM D-445	98.30
06	Viscosity @ 100 C, cSt	ASTM D-445	14.62
07	Viscosity Index	ASTM D-2270	155
08	TBN, mg KOH/gm	ASTM D-2896	12.0
09	Flash Point, COC, C	ASTM D-92	232
10	Pour Point, C	ASTM D-97	-39
10	CCS Viscosity (mPa·s)	ASTM D-5293	4926

DEOGEN SYNTHETIC SAE 15W40 API CJ-4



Health and Safety:

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application, following the recommendations provided in the Material Safety Data Sheet (MSDS). MSDSs are available upon request. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.