



GP

GENERAL PETROLEUM

www.generalpetroleum.de

Product Data Sheet (PDS)



**SYNCROGEN MTF
SYNTHETIC
SAE 75W80
API GL-5**

Published By:

Technical Department of
General Petroleum GmbH
Frankfurt, Germany

Last Update Date:

1/8/2019

SYNCROGEN MTF SYNTHETIC SAE 75W80 API GL-5



SYNCROGEN MTF **75W80 GL-5** is a fully synthetic gear lubricant formulated from synthetic base oils and an advanced additive system. It is designed for use in many manual gearboxes and provides excellent load-carrying capability where extreme pressures and shock loading are expected.

APPLICATIONS:

SYNCROGEN MTF provides excellent low temperature fluidity for safe lubrication during very low temperature transmission and transaxle startup, and also maintains a thick protective oil film during extremely hot operating conditions. Used in powered transmission and axle drives for cars, highway light and heavy-duty trucks, busses, and vans where an API GL-5 is required.

PERFORMANCE STANDARDS:

- API GL-5
- BMW MTF-1 / 2 / 3
- FORD M2C200-C / C2 / C3
- OPEL 1940757 / 68 / 76
- PAS B71 2330
- Volvo 97307/8
- Renault
- MB 235.10
- VW TL 501 50 (G 005 000/05/20/G052 911 A1/A2)

FEATURES & BENEFITS:

- **Superior Extreme Pressure Performance:**
These Oils shows excellent EP (Extreme Pressure) characteristics providing an adequate protection even under high shock loads and vibrations.
- **Excellent Resistance for Wear, Corrosion, Foaming and Oxidation:**
These Oils shows an excellent resistance against wear, corrosion and foaming as well as oxidation and ageing at elevated temperatures.

SYNCROGEN MTF SYNTHETIC SAE 75W80 API GL-5



TECHNICAL DATA

Sr. No	Characteristics	Test Method	75W80
01	Appearance	VISUAL	B & C
02	Color	ASTM D-1500	L 1.0
03	Density @ 15 C, g/ml	ASTM D-4052	0.86
04	Viscosity @ 40 C, cSt	ASTM D-445	56.26
05	Viscosity @ 100 C, cSt	ASTM D-445	9.46
06	Viscosity Index	ASTM D-2270	152
07	Flash Point, COC, C	ASTM D-92	230
08	Pour Point, C	ASTM D-97	-39

Health and Safety:

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application, following the recommendations provided in the Material Safety Data Sheet (MSDS). MSDSs are available upon request. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.