



GP

GENERAL PETROLEUM

www.generalpetroleum.de

Product Data Sheet (PDS)



**SYNCROGEN MTF
SAE 85W140
API GL-4**

Published By:

Technical Department of
General Petroleum GmbH
Frankfurt, Germany

Last Update Date:

1/8/2019

SYNCROGEN MTF SAE 85W140 API GL-4



SYNCROGEN MTF **85W140 GL 4** is a transmission fluid on a mineral oil basis with special effective additives for manual transmissions. A high load-carrying capacity guarantees an optimum gearbox lubrication even at high temperatures.

SYNCROGEN MTF **80W-140 GL-4** ensures a strong oil film for lubrication even under the most extreme dynamic conditions

SYNCROGEN MTF **80W-140 GL-4** reduces friction, prevents wear and corrosion.

PERFORMANCE STANDARDS:

SYNCROGEN 85W140 GL-4 meets and exceeds the requirements of the following specifications:

- MAN 341 Z1
- MIL-L-2105
- AGMA 9005-F16
- David Brown S1.53.101 E
- DIN51517 Part III
- U.S. Steel 224

FEATURES & BENEFITS:

- Good thermal stability protects against deposit formation and oil thickening maintaining the life and performance of lubricant and transmission
- Good anti wear and load carrying characteristics extend the life of components.
- Improved low temperature protection and gear shifts compared to monograde products.

SYNCROGEN MTF SAE 85W140 API GL-4



TECHNICAL DATA

Sr. No	Characteristics	Test Method	Results
01	Appearance	VISUAL	B & C
02	Color	ASTM D-1500	L 3.5
03	Density @ 15 C, g/ml	ASTM D-4052	0.89
04	Viscosity @ 40 C, cSt	ASTM D-445	386.82
05	Viscosity @ 100 C, cSt	ASTM D-445	26.42
06	Viscosity Index	ASTM D-2270	92
07	Flash Point, COC, C	ASTM D-92	268
08	Pour Point, C	ASTM D-97	-15

Health and Safety:

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application, following the recommendations provided in the Material Safety Data Sheet (MSDS). MSDSs are available upon request. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.