

# DEOGEN STANDARD 15W40 CF4/SJ



DEOGEN STANDARD 15W40 CF4/SJ is a high performance diesel oil containing anti-oxidants, anti-wear additives and high levels of detergent dispersants designed to protect the engine under all operating conditions. It includes shear stable viscosity improvers to maintain good protection under hot operating conditions and reduces exhaust emissions. This oil maintains excellent control of oil consumption and protects against rust and corrosion.

## APPLICATIONS:

This oil is recommended for use in naturally aspirated and turbo-charged diesel powered equipment from leading Japanese, European and American Manufacturers, mixed fleets, On-highway light and heavy-duty trucking, off highway industries including construction, mining, quarrying and Agriculture.

## PERFORMANCE STANDARD:

DEOGEN STANDARD 15W40 CF4/SJ meets and exceeds all major Japanese, European and American engine manufacturers.

TECHNICAL DATA	
SAE GRADE	15W/40
Sp. Gravity @ 15°C	0.889
Kinematic Viscosity @ 40°C cSt	122
Kinematic Viscosity @ 100°C cSt	15.80
Viscosity Index	137
TBN mgKOH/gm	12
Flash Point°C	232
Pour Point °C	-27

# DEOGEN STANDARD 15W40 CF4/SJ



## BENEFITS

- Exceptional Thermal and Oxidation Stability ensures trouble-free operation
- Reduced maintenance costs due to minimized engine overhaul periods
- Stay in grade shear stability provides wear protection and viscosity control.
- Maintains excellent control of oil consumption.
- Advanced detergency/ dispersancy leading to cleaner engines and longer component life.
- Enhanced protection against wear.

**Health and Safety:** Based on available information, this product is not expected to produce adverse effects on health when used for the intended application, following the recommendations provided in the Material Safety Data Sheet (MSDS). MSDSs are available upon request. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

Published by General Petroleum GmbH Frankfurt, Germany  
Last Updated on: April -2011