

MARGEN OUTBOARD TC & TCWIII SAE 30



MARGEN OUTBOARD TC & TCWIII SAE 30 are high quality ash less two-stroke lubricant, designed to meet the most critical requirements of all air-cooled and water-cooled engines, the latest and very strict NMMA TC-W3 demands.

APPLICATIONS:

MARGEN OUTBOARD TC & TCWIII SAE 30 meets and exceeds the requirements of all major outboard engine manufacturers : Chrysler, Evinrude, Johnson, Mercury, Mariner, U.S. Marine/Force, Sears, OMC, Suzuki, Yamaha and for motorcycles, lawn mowers, scooters, golf cars, snowmobiles, personal water craft, chain saws, and other two-stroke powered equipments .
NMMA TC-W3 , API TC, JASO FB (ISO-L-EGB)

It is well suited for engines using oil injection systems with fuel/oil mixture ratios of up to 100:1

BENEFITS:

- Minimizes piston rings from sticking to keep the engine operating smoothly and efficiently.
- Protects against piston and combustion chamber deposits, rust, and corrosion.
- Protects the piston from scuffing and preignition problems and assures good low temperature fluidity.
- Mixes easily with fuel for premix applications.

MARGEN OUTBOARD TC & TCWIII SAE 30



TECHNICAL DATA		
	TC	TCW-III
SAE GRADE	30	30
Sp. Gravity @ 15°C	0.884	0.873
Kinematic Viscosity @ 40°C cSt	105	52
Kinematic Viscosity @ 100°C cSt	11.8	8.50
Viscosity Index	100	135
Flash Point °C	160	80
Pour Point °C	-9	-18

Health and Safety: Based on available information, this product is not expected to produce adverse effects on health when used for the intended application, following the recommendations provided in the Material Safety Data Sheet (MSDS). MSDSs are available upon request. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

Published by General Petroleum GmbH Frankfurt, Germany
Last Updated on: April -2011