

# PETROGEN FULLY SYNTHETIC 5W40 SL/CF



Petrogen Fully Synthetic 5W40 SL/CF lubricant is a very high performance product, blended from fully synthetic base oils and hi quality additives. This product is designed for use on all the latest gasoline and diesel powered vehicles requiring API 5W40 SL/CF lubricants.

## APPLICATIONS:

- PETROGEN 5W-40 has been developed for all Gasoline engines (multivalve, turbocharged, with or without catalytic converter) and all Diesel engines - with or without turbo charging - in cars and light vans, which are non equipped with a Diesel particulate filter.
- PETROGEN 5W-40 is suitable for all journeys (in town, on highways and motorways) and particularly in severe conditions.
- PETROGEN 5W-40 fully adapted for all driving styles, particularly “vigorous” and high speeds in particular for “Vigorous” driving.
- PETROGEN 5W-40 is specially designed to meet the needs of the motor manufacturers requiring extended oil change intervals.

## PERFORMANCE STANDARD:

PETROGEN 5W-40 meets and exceeds the following International & OEM Specifications.

International specifications	ACEA API	ACEA : A3/B4 SL/CF
OEMs	VOLKSWAGEN BMW GENERAL MOTORS PORSCHE	VW 502.00/VW 505.00 BMW Longlife 98 GM-LL-B025

TECHNICAL DATA	
SAE GRADE	5W/40
Density kg/m <sup>3</sup>	0.891
Kinematic Viscosity mm <sup>2</sup> /s @ 40°C	85
Kinematic Viscosity mm <sup>2</sup> /s 100 @ 100°C	14
Viscosity Index	170
Pour Point, °C	-42
Flash Point COC	226

# PETROGEN FULLY SYNTHETIC 5W40 SL/CF



## BENEFITS

- Excellent engine protections, particularly against timing system wear.
- Ensures maximum engine cleanliness.
- Outstanding thermal stability, oxidation resistance eliminating any degradation even in very severe use.
- Immediate lubrication of engine parts during cold starts, leading to longer engine life.
- Meets the requirements of the manufacturers as regards extended oil change intervals.

**Health and Safety:** Based on available information, this product is not expected to produce adverse effects on health when used for the intended application, following the recommendations provided in the Material Safety Data Sheet (MSDS). MSDSs are available upon request. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

Published by General Petroleum GmbH Frankfurt, Germany  
Last Updated on: April -2011